

Part Number			d	D _{H7}	Tolerance	B	W	H	T	T ₁	dh	D ₁₉₇	Tolerance	P.C.D.	K	A	S	ℓ ₁	F	M (Coarse)(d ₂)	d ₁	H ₁
Type	Bearing No.	Seal																				
Round	623	ZZ Double Shielded	3	10	+0.0150	4	16	33	9	7	7	14	-0.006	24	27	24				M4(3.3)	6.5	3.4
	624		4	13	+ 0.0180	5	18	35	10	8	9	17	-0.024	26	28	26				M5(4.3)	8	4.4
	605		5	14		5	20	36	10	8	10	18		26	30	26						
	625		5	16		5	22	38	10	8	12	20		28	31	28						
	606		6	17	+ 0.0210	6	23	39	11	9	13	21		29	32	29						
	626		6	19		6	25	41	11	9	15	24		31	34	31						
	698			19		6	25	41	11	9	15	24	-0.007	31	34	31						
	608		8	22		7	29	45	12	10	18	27	-0.028	35	36	35						
	628			24		8	32	47	13	11	20	30		37	37	37						
	6800			19		5	25	41	10	8	15	24		31	34	31						
	6900		10	22		6	29	45	11	9	19	27		35	36	35						
	6000			26	+ 0.0210	8	34	50	13	11	22	32	-0.009	40	39	40						
	6200			30		9	38	54	14	12	24	36	-0.034	44	42	44						
	6801			21		5	29	44	10	8	17	26	-0.007	34	35	34						
	6901			24		6	31	48	11	9	21	30	-0.028	38	38	38						
	6001		12	28	+ 0.0250	8	36	52	13	11	24	34		42	40	42						
	XM27R												-0.009									
	XM28R				+ 0.0250	10	40	56	15	13	26	38	-0.034	46	43	46						
	XM29R												-0.007									
	XM30R				+ 0.0210	5	32	47	10	8	20	30	-0.034	37	37	37						
Square	6902	*1 *2VV Non- Contact Sealed Rubber Seal	15	28		7	37	57	12	10	25	35		45	45	45	2	2		M6(5.2)	9.5	5.4
	6002			32	+ 0.025	9	40	60	14	12	28	38		48	46	48						
	6202			35		11	44	64	17	15	29	42		52	49	52						
	XM25S				+ 0.021	7	38	60	12	10	27	36		48	46	48						
	XM26S												-0.009									
	XM27S		17	35	+ 0.025	10	44	66	16	14	31	42	-0.034	54	50	54				M8 (6.8)	11	6.5
	XM28S			40		12	50	72	18	16	34	48		60	54	60						
	XM29S			32		7	40	60	12	10	28	38		48	46	38						
	XM30S			37		9	47	69	15	13	34	45		56	54	51						
	6004		20	42		12	54	77	18	16	36	50		64	59	56				M10 (8.5)	14	8.6
	6204			47	+ 0.025	14	58	81	20	18	40	54	-0.01 -0.04	68	62	59						
Compact	XM25C			37		7	47	69	13	11	34	45	-0.009	56	54	51				M8 (6.8)	11	6.5
	XM26C			42		9	54	77	15	13	36	50	-0.034	64	59	56						
	XM27C		25	47		12	58	88	18	16	41	54	-0.01 -0.04	72	67	63				M10 (8.5)	14	8.6
	XM28C																					
	XM29C			52	+ 0.030	15	64	94	22	20	45	60		78	72	68				M12 (10.5)	17.5	11
	XM30C												-0.009 -0.034	64	59	56						
	6806		30	42	+ 0.025	7	54	77	13	11	36	50		72	67	63				M10 (8.5)	14	8.6
	6906			47		9	58	88	15	13	41	54		80	73	70						
	6006			55		13	66	96	20	18	48	62	-0.01 -0.04	88	79	77						
	6206			62		16	74	104	23	21	55	70										
	6007				+ 0.030	14			21	19										M12 (10.5)	17.5	11
	6207		35	72		17	88	126	26	23	64	84	-0.012 -0.047	105	95	92	3	3	51			
	6008		40	68		15	82	114	23	21	60	78	-0.01 -0.04	96	86	80	2	2	54			
	6208																					
ZZ Double Shielded	6010	ZZ Double Shielded		80	+ 0.035	18 16	96	134	27 25	24 22	74	92		113	102 -	98		3	56	M12 (10.5)	17.5	11
	6210		50	90		20	110	147	31	28	83	106	-0.012 -0.047	126	-	104	3	4	72			